



Stahl Gerlafingen AG
 Postfach
 CH-4563 Gerlafingen
 CHE-105.859.757 MWST
 info.ch@beltrame-group.com - www.gruppobeltrame.com

Declaration of performance



0063
21

0063 - CPR - 106584

1	Identification product code	Steel grade / material no.					
2	Identification of the product	Certificate, delivery note and label					
3	Intended use	Hot-rolled structural steel products for metal building structures or in composite concrete composite structures according to EN 10025-1:2004					
4	Manufacturer	Stahl Gerlafingen AG Postfach CH-4563 Gerlafingen CHE-105.859.757 MWST info.ch@beltrame-group.com - www.gruppobeltrame.com					
5	System to evaluate the performance according to regulation (EU) no 305/2011	System 2+					
6	Notified body	Kiwa Nederland B.V. Sir Winston Churchillaan 273 NL-2280 AB Rijswijk					
7	Tasks of the notified body	The notified body has performed the initial inspection of factory and factory production control and the continuous surveillance, assessment and approval of factory production control and has issued the certificate 0780-CPD-52003.					
8	Declared performance	Thickness [mm]	S235 JR/J0/J2	S275 JR/J0/J2	S235/S275 JR/J0/J2	S355 JR/J0/J2	EN 10025-2: 2019 Tolerances on dimensions and shape: Flat bars in accordance with EN 10058, wide flat bars in accordance with DIN 59200 and angles in accordance with EN 10056-1 and tolerances in accordance with EN 10056-2* European wide flange beams HEB/IPB and HEA/IPBI in accordance with DIN 1025-2 and -3 and tolerances in accordance with EN 10034 European beams IPE in accordance with DIN 1025-5 and tolerances in accordance with EN 10034 European taper flange channels UPN in accordance with DIN 1026-1 and tolerances in accordance with EN 10279
	Yield strength R_{eH} [MPa]	≤ 16 $>16 / \leq 40$	≥ 235 ≥ 225	≥ 275 ≥ 265	≥ 275 ≥ 265	≥ 355 ≥ 345	
	Tensile strength R_m [MPa]	$\geq 3 / \leq 100$	$\geq 360 / \leq 510$	$\geq 410 / \leq 560$	$\geq 410 / \leq 510$	$\geq 470 / \leq 630$	
	Elongation $A_{5,65}$ [%]	$\geq 3 / \leq 40$	≥ 26	≥ 23	≥ 26	≥ 22	
	Impact strength [J]	≤ 150	≥ 27	≥ 27	≥ 27	≥ 27	
	Weldability CEV [%]	≤ 30 $>30 / \leq 40$	≤ 0.35 ≤ 0.35	≤ 0.40 ≤ 0.40	≤ 0.35 ≤ 0.35	≤ 0.45 ≤ 0.47	
	Suitable for zinc coating	Categories B and D					
	Durability	No performance determined					
Non-radioactivity is controlled. Regulated material: No performance determined. Electric arc furnace (>95% recycling content). Environmental product declaration ICQM - 14011EPD.							
The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.							
Signed for and on behalf of Stahl Gerlafingen AG by:		Gerlafingen, 01.01.2021		 Alain Creteur Country Manager		 Dr. Christoph Zeltner Head of Improvement Management	